

HS Round Chain Block

Model		HS0.5	HS1	HS1.5	HS2	HS3	HS5	HS10	HS20	HS30
Capacity (ton)		0.5	1	1.5	2	3	5	10	20	30
Standard lifting height(m)		2.5	2.5	2.5	2.5	3	3	3	3	3
Headroom (Hook to Hook) Hmin(mm)		280	300	440	380	470	600	730	1000	1300
Chain pulls to Lift Full Load (Newton)		161	322.5	400	345	404	476	478	480	490
No. of Load chain full load		1	1	1	2	2	2	4	8	12
Diameter of load chain(mm)		6	6	8	6	8	10	10	10	10
Main dimensions(mm)	A	142	142	178	142	178	210	358	580	634
	B	122	122	139	122	139	162	162	200	282
	C	24	28	34	34	38	41	50	85	85
	D	142	142	178	142	178	210	210	210	210
Net weight(kg)		9	9.2	14.5	12.3	21.5	35	65	141	280
Package dimensions(L*W*H) (cm)		25×18×14	25×18×14	30×22×16	28×19×14	31×22×16	39×27×20	58×43×25	80×65×34	88×80×40
Extra weight perimeter of Extra Lift (KG)		1.7	1.7	2.7	2.5	3.7	5.3	9.7	19.7	28.6

