

Beiblatt zum Sicherheitsdatenblatt / Supplement to the safety data sheet

Abschnitt 1 / Section 1

- 1.1 Produktidentifikation / Product identification
- s. Original-Datenblatt / see original safety data sheet
 s. Original-Datenblatt / see original safety data sheet
 - s. Original-Datenblatt / see original safety data sheet

1.2 Verwendungen des Stoffs / Uses of the substance1.3 Einzelheiten zum Lieferanten / Details of the supplier

Firmenname /	Supplier	Stürmer Maschinen GmbH,
Straße /	Street	DrRobert-Pfleger-Str. 26,
Ort /	City	D-96103 Hallstadt
Tel. /	Phone	+49 (0)951 96555 - 0 (07:00 - 17:00 Uhr / 07:00 am - 05:00 pm)
E-Mail /	E-Mail	info@stuermer-maschinen.de

1.4 Notrufnummer / Emergency Telephone

Wählen Sie die passende Notrufnummer anhand des GHS-Symbols auf Ihrem Gefahrgut oder entsprechend Abschnitt 2.2 des orig. Sicherheitsdatenblattes *. *Call the appropriate emergency number using the GHS symbol on your dangerous goods or according to section 2.2 of the original safety data sheet *.*

GHS Gefahren- piktogramm / GHS symbol	GHS-Kürzel/ GHS-no.	Mögliche Signalwörter/ <i>Warning</i>	Gefährdungsklassen / Description of hazards	Notrufnummer */ Emergency Phone *
$ \begin{array}{c} & & & \\ & & & & \\ & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & $	GHS01 bis GHS09			+49 (0)951 96555 - 590 Sammelnotrufnummer Gefahrstoffe
	GHS01	Gefahr oder Achtung / Danger or Attention	Explosive Stoffe/Gemische und Erzeugnisse mit Explosivstoff, selbstzersetzliche Stoffe/Gemische, organische Peroxide / Explosive substances / mixtures and products containing explosives, self- reactive substances / mixtures, organic peroxides	- 591
	GHS02	Gefahr oder Achtung / Danger or Attention	Selbstzersetzliche Stoffe/Gemische, organische Peroxide, entzündbare Gase, Aerosole Flüssigkeiten, Feststoffe, selbsterhitzungsfähige Gemische, pyrophore Flüssigkeiten und Feststoffe, Stoffe/Gemische, die bei Berührung mit Wasser entzündbare Gase bilden / Self-reactive substances / mixtures, organic peroxides, flammable gases, aerosols, liquids, solids, self-heating mixtures, pyrophoric liquids and solids, substances / mixtures which form flammable gases on contact with water	- 592
	GHS03	Gefahr oder Achtung / Danger or Attention	Oxidierende Gase, Flüssigkeiten, Feststoffe / Oxidizing gases, liquids, solids	- 593
\diamond	GHS04	Achtung / Attention	Verdichtete, verflüssigte, gelöste und tiefgekühlt verflüssigte Gase / Compressed, liquefied, dissolved and refrigerated liquefied gases	- 594
	GHS05	Gefahr oder Achtung / Danger or Attention	Verätzung der Haut, schwere Augenschäden, auch metallkorrosive Eigenschaften / Chemical burns to the skin, severe eye damage, also metal-corrosive properties	- 595
	GHS06	Gefahr / Danger	Äußerst schwere und schwere akute Gesundheitsschäden oder Tod / Extremely severe and severe acute damage to health or death	- 596
	GHS07	Achtung / Attention	Akute Gesundheitsschäden, Reizung der Haut, der Augen und der Atemwege, Sensibilisierung der Haut, narkotisierende Wirkungen / Acute damage to health, irritation of the skin, eyes and the respiratory tract, sensitization of the skin, narcotic effects	- 597
	GHS08	Gefahr oder Achtung / Danger or Attention	Chronische Gesundheitsschäden (Organschädigungen) bei einmaliger oder mehrmaliger Exposition, krebserzeugende, erbgutverändernde und fort- pflanzungsgefährdende Wirkungen, Lungenschäden durch Eindringen von Substanzen in die Lunge (Aspirationsgefahr), Sensibilisierung der Atemwege / Chronic damage to health (damage to organs) after single or multiple exposure, carcinogenic, mutagenic and reproductive effects, lung damage due to the penetration of substances into the lungs (risk of aspiration), sensitization of the respiratory tract	- 598
¥2	GHS09	Achtung oder ohne Signalwort/ Attention or without wording	Giftig für Wasserorganismen mit kurz- und langfristiger Wirkung / Toxic to aquatic organisms with short and long-term effects	- 599

* 07:00 - 17:00 Uhr, außerhalb dieses Zeitraums kann die Nummer auf dem Sicherheitsdatenblatt angerufen werden / 07:00 am - 05:00 pm, outside this time, the number on the safety data sheet can be called

Für alle anderen Informationen siehe Original-Sicherheitsdatenblatt / For all other information, see the original safety data sheet





HFO-1234yf

Material Safety Data Sheet

2,3,3,3-Tetrafluoropropene, HFO-1234yf Huanxin Fluoro

1. PRODUCT AND COMPANY IDENTIFICATION

:	2,3,3,3-Tetrafluoropropene, HFO-1234yf
ration :	Refrigerant
:	HFO-1234yf
:	CF ₃ CF=CH ₂
:	Zhejiang Huanxin Fluoro Material Co., Ltd. Yanggongwan, Huajie, Yongkang, Zhejiang 321302, China Phone: 86 579 87271588 Fox. : 86 570 87271599
	: ration : : :

FOR CHEMICAL EMERGENCY: 86 579 87285499

2. HAZARDS IDENTIFICATION

Auto-ignition Temperature 405°C Slightly flammable.

Potential Health Effects

SkinContact with liquid or refrigerated gas can cause cold burns and frostbite.EyesContact with liquid or refrigerated gas can cause cold burns and frostbite.InhalationMisuse or intentional inhalation abuse may cause death without warning
symptoms, due to cardiac effects.

Other symptoms potentially related to misuse or inhalation abuse are: Anaesthetic effects, Light-headedness, dizziness, confusion, incoordination, drowsiness, or unconsciousness.

Carcinogenicity

None of the components present in this material at concentrations equal to or greater than 0.1% are listed by IARC, NTP, or OSHA, as a carcinogen.

3. COMPOSITION, INFORMATION ON INGREDIENTS

Chemical Name	CAS No	EC No.	%
2,3,3,3-Tetrafluoropropene	754-12-1	468-710-7	99.8

4. FIRST AID MEASURES

General advice	First aider needs to protect himself.
	Take off all contaminated clothing immediately.
Inhalation	When inhaled remove to fresh air and seek medical aid.
	If unconscious place in recovery position and seek medical advice.
Skin contact	Rapid evaporation of the liquid may cause frostbite.
	In case of contact with liquid, thaw frosted parts with water, then remove
	clothing carefully.
	Wash with plenty of water
	Wash contaminated clothing before re-use.
	Consult a physician.
Eye contact	Protect unharmed eye.
	Rinse immediately with plenty of water, also under the eyelids,
	for at least 15 minutes.
	Call a physician immediately.
Ingestion	Is not considered a potential route of exposure.

5. FIRE FIGHTING MEASURES

Suitable extinguishing media:
Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.
Specific hazards during fire fighting:
Slightly flammable.
Some risk may be expected of corrosive and toxic decomposition products.
In case of fire hazardous decomposition products may be produced such as:
Carbon monoxide, Hydrogen halides, Carbonyl halides

Cool closed containers exposed to fire with water spray. Heating will cause pressure rise with risk of bursting and subsequent explosion.

Special protective equipment for fire-fighters:

Wear self-contained breathing apparatus and protective suit.

Further information:

In case of fire: Evacuate area. Fight fire remotely due to the risk of explosion.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions:

Keep people away from and upwind of spill / leak. Ventilate the area. Wear self-contained breathing apparatus and protective suit.

Environmental precautions:

The product evaporates readily. Prevent product from entering drains.

Methods for cleaning up:

Use low-sparking handtools and explosion-proof electrical equipment. Allow to evaporate.

Additional advice:

Inform the responsible authorities in case of gas leakage, or of entry into waterways, soil or drains.

Pay attention to the spreading of gases especially at ground level (heavier than air) and to the direction of the wind.

For personal protection see section 8.

7. HANDLING AND STORAGE

Advice on safe handling: Exhaust ventilation at the object is necessary. Use explosion-proof equipment. Pressurized container: Protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.

Advice on protection against fire and explosion:

Use only in explosion-proof areas. Keep product and empty container away from heat and sources of ignition. Use only explosion-proof equipment. Fire or intense heat may cause violent rupture of packages.

Further information on storage conditions:

Keep containers tightly closed in a cool, well-ventilated place. Containers should be protected against falling down. Protect from warmth. Do not store at temperature exceeding 50°C. Keep away from direct sunlight.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Highly effective exhaust ventilation

Respiratory protection:

In case of insufficient ventilation wear suitable respiratory equipment.

Hand protection:	Wear suitable gloves. Heat insulating gloves.
Eye protection:	Goggles.
Skin and body protection:	Wear suitable protective equipment.
Hygiene measures:	Provide adequate ventilation. Do not smoke. When using do not eat or drink.

9. PHYSICAL AND CHEMICAL PROPERTIES

Form	Compressed liquefied gas
Colour	Colourless
Odour	Slight, ether-like
Molecular Weight	114g/mol
РН	Neutral
Melting Point	-152.2 °C
Boiling Point, T _b	-29.4°C
Vapour Pressure	5,830 hPa at 20°C
Density	4.8 kg/m ³ at 20 °C
	Vapour density

Flash point	Not applicable
Auto-ignition Temperature	405 °C at 1,013 hPa
Lower Explosion Limit	6.2 vol% at 21 °C
Upper Explosion Limit	12.3 vol% at 21 °C at 1013 hPa
Water Solubility	198.2 mg/l at 24°C
Partition Coefficient	Noctanol / Water POW: 2 at 25°C
Relative Vapour Density	4 (Air=1.0)
Evaporation Rate	Not determined.
Critical Point	95℃
P _{vap} , MPa (25°C)	0.673
P _{vap} , MPa (80℃)	2.47
Liquid Density, kg/m ³ (25°C)	1094
Vapor Density, kg/m ³ (25°C)	37.6
ODP	0
GWP	4
Atmospheric Lifetime	11 Days

10. STABILITY AND REACTIVITY

Conditions to avoid:

Keep away from: Heat, flames and sparks. Do not spray on a naked flame or any incandescent material. Gas cylinder : Keep at temperature not exceeding 52°C. Pressurized container: Do not pierce or burn, even after use.

Materials to avoid:

Reactions with alkali metals. Reactions with light metals. Finely divided aluminium Zinc Magnesium

Hazardous decomposition products:

Risk of formation of toxic pyrolysis products containing fluorine. Carbon Monoxide Carbon Dioxide (CO₂) Carbonyl Halides Hydrogen Halides

11. TOXICOLOGICAL INFORMATION

Acute inhalation toxicity : LC50

Species: rat
Does: > 400,000 ppm
Exposure time: 4h

Skin irritation	:	Slight irritation
Eye irritation	:	Slight irritation
Repeated dose toxicity	:	Species: rat Route of exposure: Inhalation NOEL: 233mg/kg NOEL: 50000 ppm

Further information:

Concentration above the admissible concentration at the workplace may cause dizziness, headache and inebriation. 2,3,3,3-Tetrafluoropropene: Mouse Micronucleus (4-hour): No toxicological significant signs reported. No increase in the frequency of micronuclei. Cardiac Sensitization: No effects for exposures up to 12% (120,189ppm).

12. ECOLOGICAL INFORMATION

Aquatic Toxicity		
96 h LC50	:	Cyprinus carpio (Carp) > 197 mg/l
72 h NOEC	:	Algae > 100 mg/l
48 h EC50	:	Daphnia magna (Water flea) > 100 mg/l
Environmental Fate		
Biodegradability a	erobic :	< 5 % OECD Test Guideline 301F
		According to the results of tests of biodegradability this product is not readily biodegradable.
Bioaccumulation	:	No bioaccumulation is to be expected (log Pow <= 4).

13. DISPOSAL CONSIDERATIONS

Product:Dispose according to legal requirements.Packaging:Legal requirements are to be considered in regard of reuse or disposal of
used packaging materials.

14. TRANSPORT INFORMATION

UN number 3161

iquefied Gas, Flammable, N.O.S.
(2,3,3,3-Tetrafluoropropene)
1
1

15. REGULATORY INFORMATION

TSCA 5E

This material contains one or more substances which are subject to a TSCA Section 5 Consent Order or Significant New Use Rule (SNUR).

TSCA 12B

This material contains one or more substances which requires export notification under TSCA Section 12(b) and 40 CFR Part 707 Subpart D

The approved uses are: refrigerant in motor vehicle air conditioning systems.

Processors and users of this substance must also comply with the applicable general SNUR requirements set forth in 40 CFR 721 subpart A, including export notification requirements if applicable (40 CFR 721.20), and the applicable record keeping requirements set forth at 40 CFR 721.125.

SARA 313 Regulated Chemical(s)

This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

California Prop. 65

Chemicals known to the State of California to cause cancer, birth defects or any other harm: none known

16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct of the best of our knowledge, information and belief at the date of its publication. The information give is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid such material used in combination with any other materials or in any process, unless specified in the text. Final determination of suitability of any materials is the sole responsibility of the user.

This information should not constitute a guarantee for any specific product properties.