

# Beiblatt zum Sicherheitsdatenblatt / Supplement to the safety data sheet

## Abschnitt 1 / Section 1

### 1.1 Produktidentifikation / Product identification

s. Original-Datenblatt / see original safety data sheet

### 1.2 Verwendungen des Stoffs / Uses of the substance











s. Original-Datenblatt / see original safety data sheet

### 1.3 Einzelheiten zum Lieferanten / Details of the supplier

Firmenname /	Supplier	Stürmer Maschinen GmbH,
Straße /	Street	Dr.-Robert-Pfleger-Str. 26,
Ort /	City	D-96103 Hallstadt
Tel. /	Phone	+49 (0)951 96555 - 0 (07:00 - 17:00 Uhr / 07:00 am - 05:00 pm)
E-Mail /	E-Mail	info@stuermer-maschinen.de

### 1.4 Notrufnummer / Emergency Telephone

Wählen Sie die passende Notrufnummer anhand des GHS-Symbols auf Ihrem Gefahrgut oder entsprechend Abschnitt 2.2 des orig. Sicherheitsdatenblattes \*.  
Call the appropriate emergency number using the GHS symbol on your dangerous goods or according to section 2.2 of the original safety data sheet \*.

GHS Gefahren-piktogramm / GHS symbol	GHS-Kürzel/ GHS-no.	Mögliche Signalwörter/ Warning	Gefährdungsklassen / Description of hazards	Notrufnummer */ Emergency Phone *
	GHS01 bis GHS09			+49 (0)951 96555 - 590 Sammelnotrufnummer Gefahrstoffe
	GHS01	Gefahr oder Achtung / Danger or Attention	Explosive Stoffe/Gemische und Erzeugnisse mit Explosivstoff, selbstzersetzliche Stoffe/Gemische, organische Peroxide / Explosive substances / mixtures and products containing explosives, self-reactive substances / mixtures, organic peroxides	- 591
	GHS02	Gefahr oder Achtung / Danger or Attention	Selbstzersetzliche Stoffe/Gemische, organische Peroxide, entzündbare Gase, Aerosole Flüssigkeiten, Feststoffe, selbsterhitzungsfähige Gemische, pyrophore Flüssigkeiten und Feststoffe, Stoffe/Gemische, die bei Berührung mit Wasser entzündbare Gase bilden / Self-reactive substances / mixtures, organic peroxides, flammable gases, aerosols, liquids, solids, self-heating mixtures, pyrophoric liquids and solids, substances / mixtures which form flammable gases on contact with water	- 592
	GHS03	Gefahr oder Achtung / Danger or Attention	Oxidierende Gase, Flüssigkeiten, Feststoffe / Oxidizing gases, liquids, solids	- 593
	GHS04	Achtung / Attention	Verdichtete, verflüssigte, gelöste und tiefgekühlt verflüssigte Gase / Compressed, liquefied, dissolved and refrigerated liquefied gases	- 594
	GHS05	Gefahr oder Achtung / Danger or Attention	Verätzung der Haut, schwere Augenschäden, auch metallkorrosive Eigenschaften / Chemical burns to the skin, severe eye damage, also metal-corrosive properties	- 595
	GHS06	Gefahr / Danger	Äußerst schwere und schwere akute Gesundheitsschäden oder Tod / Extremely severe and severe acute damage to health or death	- 596
	GHS07	Achtung / Attention	Akute Gesundheitsschäden, Reizung der Haut, der Augen und der Atemwege, Sensibilisierung der Haut, narkotisierende Wirkungen / Acute damage to health, irritation of the skin, eyes and the respiratory tract, sensitization of the skin, narcotic effects	- 597
	GHS08	Gefahr oder Achtung / Danger or Attention	Chronische Gesundheitsschäden (Organschädigungen) bei einmaliger oder mehrmaliger Exposition, krebserzeugende, erbgutverändernde und fortpflanzungsgefährdende Wirkungen, Lungenschäden durch Eindringen von Substanzen in die Lunge (Aspirationsgefahr), Sensibilisierung der Atemwege / Chronic damage to health (damage to organs) after single or multiple exposure, carcinogenic, mutagenic and reproductive effects, lung damage due to the penetration of substances into the lungs (risk of aspiration), sensitization of the respiratory tract	- 598
	GHS09	Achtung oder ohne Signalwort / Attention or without wording	Giftig für Wasserorganismen mit kurz- und langfristiger Wirkung / Toxic to aquatic organisms with short and long-term effects	- 599

\* 07:00 - 17:00 Uhr, außerhalb dieses Zeitraums kann die Nummer auf dem Sicherheitsdatenblatt angerufen werden / 07:00 am - 05:00 pm, outside this time, the number on the safety data sheet can be called

Für alle anderen Informationen siehe Original-Sicherheitsdatenblatt / For all other information, see the original safety data sheet



# SAFETY DATA SHEET

Issuing Date 11-Nov- 2014

Revision Date 11-Nov-2014

Revision Number 1

## 1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

### Product identifier

Product SDS Name Steel Reinforced Epoxy Resin – Twin Tubes - Part A

### J-B Weld FG SKU Part Numbers Covered

8265, 8265F, 8276, 8276F, 8265S, 8265A, 8265H, 8272, 8272F, 8280, 8280F, 8281, 80165, 7265S, 7280, 8276A, 8273H, 8270, 8270F, 8271, 80176, 7276, 7270

### J-B Weld Product Names Covered

J-B Weld™ (all Twin Tubes), KwikWeld™ (all Twin Tubes), MarineWeld™ (Twin Tubes Only)

### J-B Weld Product Type

Steel Reinforced Epoxy

### Recommended use of the chemical and restrictions on use

Recommended Use General Purpose Adhesive

Uses advised against No information available

### Details of the supplier of the safety data sheet

Supplier Name J-B WELD COMPANY,LLC  
Supplier Address 1130 COMO ST  
SULPHUR SPRINGS, TX 75482  
USA

### **Emergency Telephone Numbers**

Transportation Emergencies: Chemtrec (24 hour transportation emergency response info):  
800-424-9300 or 703-527-3887

Poison/Medical Emergencies: Poison Control Centers (24 hour emergency poison / medical  
response info): 800-222-1222

Supplier Email [info@jbweld.com](mailto:info@jbweld.com)

Supplier Phone Number 903-885-7696

## 2. HAZARDS IDENTIFICATION

### OSHA/HCS status

This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

### Classification of the substance or mixture GHS label elements

SKIN CORROSION/IRRITATION - Category 2  
SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2B  
SKIN SENSITIZATION - Category 1



### Hazard pictograms

#### Signal word

Warning!

#### Hazard statements

Causes skin and eye irritation.  
May cause an allergic skin reaction.

### Precautionary statements

#### Prevention

Wear protective gloves. Wear eye or face protection. Avoid breathing dust. Wash hands thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace.

#### Response

IF ON SKIN: Wash with plenty of soap and water. Take off contaminated clothing. Wash contaminated clothing before reuse. If skin irritation or rash occurs: Get medical attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention.

#### Storage

Not applicable.

#### Disposal

Dispose of contents and container in accordance with all local, regional, national and international regulations.

#### Hazards not otherwise classified

None known.

## 3. COMPOSITION/INFORMATION ON INGREDIENTS

#### Substance/mixture

Mixture

Ingredient name	% by weight	CAS number
reaction product: bisphenol-A-(epichlorhydrin); epoxy resin	10 - 30	25068-38-6
crystalline silica non-respirable	0.1 - 1	14808-60-7
carbon black respirable	0.1 - 1	1333-86-4

Occupational exposure limits, if available, are listed in Section 8.

## 4. FIRST AID MEASURES

### Description of necessary first aid measures

#### Inhalation

Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention if adverse health effects persist or are severe. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

#### Skin contact

Wash with plenty of soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.

#### Eye contact

Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.

#### Ingestion

Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention if adverse health effects persist or are severe. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

### Most important symptoms/effects, acute and delayed

### Potential acute health effects

#### Inhalation

No known significant effects or critical hazards.

#### Skin contact

Causes skin irritation. May cause an allergic skin reaction.

#### Eye contact

Causes serious eye irritation.

#### Ingestion

Irritating to mouth, throat and stomach.

### Over-exposure signs/symptoms

<b>Inhalation</b>	No specific data.
<b>Skin contact</b>	Adverse symptoms may include the following: irritation redness
<b>Eye contact</b>	Adverse symptoms may include the following: pain or irritation watering redness
<b>Ingestion</b>	No specific data.

### Indication of immediate medical attention and special treatment needed, if necessary

**Notes to physician** Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.

**Specific treatments** No specific treatment.

See toxicological information (Section 11)

## 5. FIRE-FIGHTING MEASURES

### Extinguishing media

<b>Suitable extinguishing media</b>	Use an extinguishing agent suitable for the surrounding fire.
<b>Unsuitable extinguishing media</b>	None known.

**Specific hazards arising from the chemical** No specific fire or explosion hazard.

### National Fire Protection Association (U.S.A.)



### **Hazardous thermal decomposition products**

Decomposition products may include the following materials:  
carbon dioxide  
carbon monoxide  
halogenated compounds  
metal oxide/oxides

### **Special protective actions for fire-fighters**

Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

### **Special protective equipment for fire-fighters**

Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

## 6. ACCIDENTAL RELEASE MEASURES

### Personal precautions, protective equipment and emergency procedures

#### For non-emergency personnel

No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

#### For emergency responders

If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

#### Environmental precautions

Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

### Methods and materials for containment and cleaning up

#### Small spill

Move containers from spill area. Avoid dust generation. Using a vacuum with HEPA filter will reduce dust dispersal. Place spilled material in a designated, labeled waste container. Dispose of via a licensed waste disposal contractor.

#### Large spill

Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Avoid dust generation. Do not dry sweep. Vacuum dust with equipment fitted with a HEPA filter and place in a closed, labeled waste container. Dispose of via a licensed waste disposal contractor. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

## 7. HANDLING AND STORAGE

### Conditions for safe storage, including any incompatibilities

Do not store below the following temperature: 35°C (95°F). Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

### Precautions for safe handling

#### Protective measures

Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not ingest. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

#### Advice on general occupational hygiene

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### Control parameters

### Occupational exposure limits

Ingredient name	CAS #	Exposure limits
crystalline silica non-respirable	14808-60-7	<b>OSHA PEL Z3 (United States, 9/2005). Notes: 250/(%SiO<sub>2</sub>+5)</b> TWA: 250 MPPCF / (%SiO <sub>2</sub> +5) 8 hours. Form: Respirable <b>OSHA PEL Z3 (United States, 9/2005). Notes: 10/(SiO<sub>2</sub>+2)</b> TWA: 10 MG/M3 / (%SiO <sub>2</sub> +2) 8 hours. Form: Respirable <b>ACGIH TLV (United States, 3/2012).</b> TWA: 0.025 mg/m <sup>3</sup> 8 hours. Form: Respirable fraction <b>NIOSH REL (United States, 1/2013).</b> TWA: 0.05 mg/m <sup>3</sup> 10 hours. Form: respirable dust <b>OSHA PEL Z3 (United States, 9/2005). Notes: 30/(%SiO<sub>2</sub>+2)</b> TWA: 30 MG/M3 / (%SiO <sub>2</sub> +2) 8 hours. Form: Total dust.
carbon black respirable	1333-86-4	<b>OSHA PEL 1989 (United States, 3/1989).</b> TWA: 3.5 mg/m <sup>3</sup> 8 hours. <b>ACGIH TLV (United States, 6/2013).</b> TWA: 3 mg/m <sup>3</sup> 8 hours. Form: Inhalable fraction <b>NIOSH REL (United States, 10/2013).</b> TWA: 3.5 mg/m <sup>3</sup> 10 hours. TWA: 0.1 mg of PAHs/cm <sup>3</sup> 10 hours. <b>OSHA PEL (United States, 2/2013).</b> TWA: 3.5 mg/m <sup>3</sup> 8 hours.

### Appropriate engineering controls

No special ventilation requirements. Good general ventilation should be sufficient to control worker exposure to airborne contaminants. If this product contains ingredients with exposure limits, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure below any recommended or statutory limits.

### Environmental exposure controls

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

### Individual protection measures

#### Hygiene measures

Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

#### Respiratory protection

Use a properly fitted, particulate filter respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

#### Skin protection

#### Hand protection

Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

#### Body protection

Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

**Other skin protection**

Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

**Eye/face protection**

Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases, or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

**Physical state**

Solid.

**Color**

Black. [Dark]

**Odor**

Ethereal. [Slight]

**Odor threshold**

Not available.

**pH**

Not available.

**Melting point**

Not available.

**Boiling point**

Not available.

**Flash point**

Closed cup: >93.3°C (>199.9°F) [Setaflash.] [Product does not sustain combustion.]

**Evaporation rate**

Not available.

**Flammability (solid, gas)**

Extremely flammable in the presence of the following materials or conditions: open flames, sparks and static discharge.

Non-flammable in the presence of the following materials or conditions: heat, shocks and mechanical impacts, oxidizing materials, reducing materials, combustible materials, organic materials, metals, acids, alkalis and moisture.

**Lower and upper explosive (flammable) limits**

Not available.

**Vapor pressure**

Not available.

**Vapor density**

Not available.

**Relative density**

1.927

**Solubility**

Insoluble in the following materials: cold water and hot water.

**Solubility in water**

Not available.

**Auto-ignition temperature**

Not available.

**Decomposition temperature**

>220°C (>428°F)

**Viscosity**

Not available.

**VOC (% content)**

<1%

## 10. STABILITY AND REACTIVITY

**Reactivity**

No specific test data related to reactivity available for this product or its ingredients.

**Chemical stability**

The product is stable.

**Possibility of hazardous reactions**

Under normal conditions of storage and use, hazardous reactions will not occur.

**Conditions to avoid**

No specific data

**Incompatible materials**

No specific data

**Hazardous decomposition products**

Under normal conditions of storage and use, hazardous decomposition products should not be produced.



## 11. TOXICOLOGICAL INFORMATION

### Information on toxicological effects

#### Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
carbon black respirable	LD50 Oral	Rat	>15400 mg/kg	-

#### Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
reaction product: bisphenol-A(epichlorhydrin); epoxy resin	Eyes - Mild irritant	Rabbit	-	100 milligrams	-
	Skin - Moderate irritant	Rabbit	-	24 hours 500 microliters	-
	Skin - Severe irritant	Rabbit	-	24 hours 2 milligrams	-

#### Sensitization

No specific data.

#### Mutagenicity

No specific data.

#### Carcinogenicity

No specific data.

#### Classification

Product/ingredient name	OSHA	IARC	NTP
crystalline silica nonrespirable	-	1	Known to be a human carcinogen.
carbon black respirable	-	2B	-

#### Reproductive toxicity

No specific data.

#### Teratogenicity

No specific data.

#### Specific target organ toxicity (single exposure)

No specific data.

#### Specific target organ toxicity (repeated exposure)

No specific data.

#### Aspiration hazard

No specific data.

#### Information on the likely routes of exposure

Not available.

#### Potential acute health effects

##### Eye contact

Causes serious eye irritation.

##### Inhalation

No known significant effects or critical hazards.

##### Skin contact

Causes skin irritation. May cause an allergic skin reaction.

##### Ingestion

Irritating to mouth, throat and stomach.

#### Symptoms related to the physical, chemical and toxicological characteristics





<b>Eye contact</b>	Adverse symptoms may include the following: pain or irritation watering redness
<b>Inhalation</b>	No specific data.
<b>Skin contact</b>	Adverse symptoms may include the following: irritation redness
<b>Ingestion</b>	No specific data.
<b>Delayed and immediate effects and also chronic effects from short and long term exposure</b>	
<b><u>Short term exposure</u></b>	
<b>Potential immediate effects</b>	Not available.
<b>Potential delayed effects</b>	Not available.
<b><u>Long term exposure</u></b>	
<b>Potential immediate effects</b>	Not available.
<b>Potential delayed effects</b>	Not available.
<b><u>Potential chronic health effects</u></b>	No specific data.
<b>General</b>	Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.
<b>Carcinogenicity</b>	No known significant effects or critical hazards.
<b>Mutagenicity</b>	No known significant effects or critical hazards.
<b>Teratogenicity</b>	No known significant effects or critical hazards.
<b>Developmental effects</b>	No known significant effects or critical hazards.
<b>Fertility effects</b>	No known significant effects or critical hazards.
<b><u>Numerical measures of toxicity</u></b>	
<b>Acute toxicity estimates</b>	No specific data.

## 12. ECOLOGICAL INFORMATION

### Toxicity

No specific data.

### Persistence and degradability

No specific data.

### Bioaccumulative potential

Product/ingredient name	LogP <sub>ow</sub>	BCF	Potential
reaction product: bisphenol-A(epichlorhydrin); epoxy resin	2.64 to 3.78	31	low

### Mobility in soil

Soil/water partition coefficient (K<sub>oc</sub>)      Not available.

**Other adverse effects**                      No known significant effects or critical hazards.

## 13. DISPOSAL CONSIDERATIONS



**Disposal methods**

The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

**RCRA classification**

Not available.

## 14. TRANSPORT INFORMATION

	<b>DOT Classification</b>	<b>TDG Classification</b>	<b>Mexico Classification</b>	<b>IMDG</b>	<b>IATA</b>
<b>UN Number</b>	Not regulated.	Not regulated.	Not regulated.	Not regulated.	Not regulated.
<b>UN proper shipping name</b>	-	-	-	-	-
<b>Transport hazard class(es)</b>	-	-	-	-	-
<b>Packing group</b>	-	-	-	-	-
<b>Environmental hazards</b>	No.	No.	No.	No.	No.
<b>Additional information</b>	-	-	-	-	-

**Special precautions for user**

**Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

## 15. REGULATORY INFORMATION

**U.S. Federal regulations**

**TSCA 8(a) PAIR:** Siloxanes and Silicones, di-Me, reaction products with silica

**TSCA 9(a) CDR Exempt/partial exemption:** Not determined

**United States Inventory (TSCA 8b):** All components are listed or exempted.

**Clean Air Act Section 112(b) Hazardous Air Pollutants (HAPs)**

Not listed

**Clean Air Act Section 602 Class I Substances**

Not listed

**Clean Air Act Section 602 Class II Substances**

Not listed

**SARA 302/304****Composition/information on ingredients**

No products were found.

**SARA 304 RQ**

Not applicable



**Classification**

Immediate (acute) health hazard

**Composition / information on ingredients**

Name	%	Fire hazard	Sudden release of pressure	Reactive	Immediate (acute) health hazard	Delayed (chronic) health hazard
reaction product: bisphenol-A-(epichlorhydrin); epoxy resin	10-30	No.	No.	No.	Yes.	No.
crystalline silica non-respirable	0.1-1	No.	No.	No.	No.	Yes
carbon black respirable	0.1-1	No.	No.	No.	No.	Yes.

**State regulations****Massachusetts**

The following components are listed: CALCIUM CARBONATE

**New York**

None of the components are listed.

**New Jersey**The following components are listed: CALCIUM CARBONATE; LIMESTONE, SILICA, QUARTZ; QUARTZ (SiO<sub>2</sub>); CARBON BLACK**Pennsylvania**The following components are listed: LIMESTONE; QUARTS (SiO<sub>2</sub>); CARBON BLACK**Minnesota Hazardous Substances**

None of the components are listed.

**California Prop. 65****WARNING: This product contains a chemical known to the State of California to cause cancer.**

Ingredient Name	Cancer	Reproductive	No significant risk level	Maximum acceptable dosage level
crystalline silica non-respirable	Yes.	No.	No.	No.
carbon black respirable	Yes.	No.	No.	No.

**Canada inventory**

All components are listed or exempted.

**International regulations****International lists****Australia inventory (AICS):** All components are listed or exempted.**China inventory (IECSC):** All components are listed or exempted.**Japan inventory:** Not determined.**Korea inventory:** All components are listed or exempted.**Malaysia Inventory (EHS Register):** Not determined.**New Zealand Inventory of Chemicals (NZIoC):** Not determined.**Phillipines inventory (PICCS):** All components are listed or exempted.**Taiwan inventory (CSNN):** Not determined.**Substances of very high concern**

None of the components are listed.

**16. OTHER INFORMATION****Key to abbreviations**

ATE = Acute Toxicity Estimate



BCF = Bioconcentration Factor  
GHS = Globally Harmonized System of Classification and Labelling of Chemicals  
IATA = International Air Transport Association  
IBC = Intermediate Bulk Container  
IMDG = International Maritime Dangerous Goods  
LogPow = logarithm of the octanol/water partition coefficient  
MARPOL 73/78 = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)  
UN = United Nations

**NON-WARRANTY:** The information presented in this publication is based upon the research and experience of J-B Weld Company. No representation or warranty is made, however, concerning the accuracy or completeness of the information presented in this publication. J-B Weld Company makes no warranty or representation of any kind, express or implied, including without limitation any warranty of merchantability or fitness for any particular purpose, and no warranty or representation shall be implied by law or otherwise. Any products sold by J-B Weld Company are not warranted as suitable for any particular purpose to the buyer. The suitability of any products for any purpose particular to the buyer is for the buyer to determine. J-B Weld Company assumes no responsibility for the selection of products suitable to the particular purposes of any particular buyer. J-B Weld Company shall in no event be liable for any special, incidental, or consequential damages.



# MSDS

## SECTION 1 – Chemical Product and Company Identification

J-B Weld Company

**P.O. Box 483**  
**1130 Como Street**  
**Sulphur Springs, TX 75482**  
**Tel: (903) 885-7696**  
**Fax: (903) 885-5911**

<b>PRODUCT NAME:</b>	<b>JB Weld Epoxy Steel Hardener</b>
<b>PRODUCT CODE:</b>	<b>(48008), 48105, 48155, 48171</b>
<b>SYNONYM/CROSS REFERENCE:</b>	<b>Epoxy Steel Hardener</b>
<b>SCHEDULE B NUMBER:</b>	<b>3214.10.0090</b>

## SECTION 2 – Hazard Identification

**OVEREXPOSURE EFFECTS:**

**ACUTE EFFECTS:**

**EYES:** Contact with eyes can cause severe irritation, possible irreparable eye damage.

**SKIN:** Contact with skin can cause irritation, (minor itching, burning and/or redness), Dermatitis, defatting may be readily absorbed through the skin.

**INHALATION:** Inhalation of vapors can cause nasal and respiratory irritation, dizziness, weakness, fatigue, nausea, headache, possible unconsciousness and/or asphyxiation. Aspiration of material into lungs may result in chemical pneumonitis which can be fatal.

**INGESTION:** Ingestion can cause gastrointestinal irritation, nausea, vomiting, diarrhea.

**PRIMARY ROUTES OF EXPOSURE:** skin, inhalation

## SECTION 3 – Composition, Information or Ingredients

<u>INGREDIENTS</u>	<u>WGT%</u>	<u>CAS #</u>
Furfuryl Alcohol	1-5%	98-00-0
Calcium Carbonate	5-10%	1317-65-3, 471-34-1
Non-fibrous Talc	15-25%	14807-96-6
Barium Sulfate	20-30%	7727-43-7
Aminophenols	1-5 %	Mixture
Polyamide Resin	15-25%	68410-23-1
Titanium Dioxide	1-5%	13463-67-7

## SECTION 4 – First Aid Measures

**INHALATION:** If inhaled, remove victim from exposure to a well-ventilated area. Make them comfortably warm, but not hot. Use oxygen or artificial respiration as required. Consult a physician.

**SKIN:** For skin contact, wash promptly with soap and excess water.

**EYES:** For eye contact, flush promptly with excess water for at least fifteen minutes. Consult a physician.

**INGESTION:** If ingested, do not induce vomiting. Give victim a glass of water. Call a physician immediately.

# MSDS

## **SECTION 5 – Fire-Fighting Measures**

FLASH POINT: >200°F/93°C Seta Flash Closed cup

LOWER FLAMMABLE LIMIT %: N/E

UPPER FLAMMABLE LIMIT %: N/E

FIRE EXTINGUISHING MEDIA: Carbon Dioxide, Dry Chemical, Foam

SPECIAL FIRE FIGHTING PROCEDURES: Fight like a fuel oil fire. Cool fire exposed containers with water spray. Firefighter should wear OSHA/NIOSH approved self-contained breathing apparatus.

UNUSUAL FIRE AND EXPLOSION HAZARD: Closed containers exposed to high temperatures, such as fire conditions may rupture.

## **SECTION 6 – Accidental Release Measures**

SPILLS, LEAK OR RELEASE: Ventilate area. Remove all possible sources of ignition. Avoid prolonged breathing of vapor. Contain spill with inert absorbent.

## **SECTION 7 – Handling and Storage**

STORAGE AND HANDLING: Use with adequate ventilation. Avoid contact with eyes and skin. Avoid breathing vapors. Do not store the product above 100°F/38°C. Do not flame, cut, braze weld or melt empty containers. Keep the product away from heat, open flame, and other sources of ignition. Avoid contact with strong acids, alkalis, and oxidizers.

## **SECTION 8 – Exposure Controls and Personal Protection**

<b><u>INGREDIENTS</u></b>	<b><u>CAS #</u></b>	<b><u>TLV/PEL</u></b>
Calcium Carbonate	1317-65-3	ACGIH TWA 10 mg/m <sup>3</sup> OSHA PEL 15 mppcf
	471-34-1	
Non-fibrous Talc	14807-96-6	ACGIH TWA 2 mg/m <sup>3</sup> OSHA PEL 20 mppcf
Barium Sulfate	7727-43-7	ACGIH TWA 10 mg/m <sup>3</sup> OSHA 15 mg/m <sup>3</sup> Total dust OSHA 15 mg/m <sup>3</sup> Respirable dust
Aminophenols	Mixture	N/E
Polyamide Resin	68410-23-1	N/E
Titanium Dioxide	13463-67-7	ACGIH TWA 10 mg/m <sup>3</sup> OSHA PEL 20 mg/m <sup>3</sup>
Furfuryl Alcohol	98-00-0	ACGIH TWA 10 ppm

RESPIRATORY PROTECTION: If component TLV limits are exceeded, use NIOSH/MSHA approved respirator to remove vapors. Use an air-supplied respirator if necessary.

VENTILATION: Use adequate ventilation in volume and pattern to keep TLV/PEL below recommended levels. Explosion-proof ventilation may be necessary.

PROTECTIVE GLOVES: To prevent prolonged exposure use rubber gloves; solvents may be absorbed through the skin.

EYE PROTECTION: Safety Glasses or goggles with splash guards or side shields.

OTHER PROTECTIVE EQUIPMENT: Wear protective clothing as required to prevent skin contact.

# MSDS

## **ACTION 9 – Physical and Chemical Properties**

APPEARANCE: White Paste

SPECIFIC GRAVITY: 1.78

VAPOR PRESSURE (mmHG): Heavier than air

BOILING POINT: N/A

VAPOR DENSITY: Heavier than air

EVAPORATION RATE (Ethyl Ether = 1): Slower than Ethyl Ether

VOLATILES BY WEIGHT:

SOLUBILITY IN WATER: None

VOC: Grams/Liter = 72

Lbs/Gallon = 0.6

## **SECTION 10 – Stability and Reactivity**

STABILITY: Stable

CONDITIONS TO AVOID: Open flames, sparks, heat, electrical and static discharge.

INCOMPATIBILITY MATERIALS TO AVOID: Strong acids, alkalis, oxidizers.

HAZARDOUS DECOMPOSITION PRODUCTS: Carbon Dioxide, Carbon Monoxide, and Carbon.

HAZARDOUS POLYMERIZATION: Will not occur.

## **SECTION 11 – Toxicological Information**

### **CHRONIC EFFECTS:**

Overexposure to this material has apparently been known to cause the following effects in lab animals: Eye, skin, lung, and central nervous system damage.

CARCINOGEN: YES \_\_\_ NO X

TERATOGEN: YES \_\_\_ NO X

MUTAGEN: YES \_\_\_ NO X

## **SECTION 12 – Ecological Information**

NOT A MARINE POLLUTANT

## **SECTION 13 – Disposal Considerations**

WASTE DISPOSAL: Dispose of in accordance with local, state, and federal regulations.

## **SECTION 14 – Transport Information**

### **For Ground Transport: In USA**

Not Regulated

### **For Air Transport:**

Not Regulated

### **For Ocean Transport:**

Not Regulated



# MSDS

## **SECTION 15 – Regulatory Information**

### **CALIFORNIA PROPOSITION 65:**

Trace amounts of some chemicals known to the State of California to cause cancer, birth defects, or other reproductive harm may be present in this product.

### **SECTION 313 SUPPLIER NOTIFICATION:**

This product contains the following toxic chemicals subject to the reporting requirements of the Emergency Planning and Community Right-To-Know Act of 1986 and 40 CFR 372:

<u>CHEMICAL NAME</u>	<u>CAS</u>	<u>% BY WGT</u>
----------------------	------------	-----------------

N/Ap

This information must be included in all MSDS that are copied and distributed for this chemical.

## **SECTION 16 – Other Information**

HMIS RATING:	Health	2	4 = Extreme
	Fire	1	3 = High
	Reactivity	1	2 = Moderate
			1 = Slight
			0 = Insignificant

Personal Protection - See Section VIII

## **ABBREVIATIONS**

IARC	= International Agency for Research on Cancer
ACGIH	= American Conference of Governmental Industrial Hygienists
NIOSH	= National Institute of Occupational Safety and Health
TLV	= Threshold Limit Value
PEL	= Permissible Emission Level
DOT	= Department of Transportation
NTP	= National Toxicology Program
N/AV	= Not Available
N/AP	= Not Applicable
N/E	= Not Established
N/D	= Not Determined

# MSDS

PREPARED BY:

J-B Weld Company

**P.O. Box 483**

**1130 Como Street**

**Sulphur Springs, TX 75482**

**Tel: (903) 885-7696**

**Fax: (903) 885-5911**

DATE REVIEWED:

February 6, 2009

DATE REVISED:

February 6, 2009

REVISION:

New Format

The information in the Material Safety Data Sheet has been compiled from our experience and from data presented in various technical publications. It is the user's responsibility to determine the suitability of this information for the adoption of the safety precautions as may be necessary. We reserve the right to revise Material Safety Data Sheets from time to time as new technical information becomes available. The user has the responsibility to contact the Company to make sure that the MSDS is the latest one issued.