

# Beiblatt zum Sicherheitsdatenblatt / Supplement to the safety data sheet

## Abschnitt 1 / Section 1

### 1.1 Produktidentifikation / Product identification

### 1.2 Verwendungen des Stoffs / Uses of the substance

### 1.3 Einzelheiten zum Lieferanten / Details of the supplier

Firmenname / Supplier: Stürmer Maschinen GmbH,  
 Straße / Street: Dr.-Robert-Pfleger-Str. 26,  
 Ort / City: D-96103 Hallstadt  
 Tel. / Phone: +49 (0)951 96555 - 0 (07:00 - 17:00 Uhr / 07:00 am - 05:00 pm)  
 E-Mail / E-Mail: info@stuermer-maschinen.de

### 1.4 Notrufnummer / Emergency Telephone

Wählen Sie die passende Notrufnummer anhand des GHS-Symbols auf Ihrem Gefahrgut oder entsprechend Abschnitt 2.2 des orig. Sicherheitsdatenblattes \*. Call the appropriate emergency number using the GHS symbol on your dangerous goods or according to section 2.2 of the original safety data sheet \*.

GHS Gefahrenpiktogramm / GHS symbol	GHS-Kürzel/ GHS-no.	Mögliche Signalwörter/ Warning	Gefährdungsklassen / Description of hazards	Notrufnummer */ Emergency Phone *
	GHS01 bis GHS09			+49 (0)951 96555 - 590 Sammelnotrufnummer Gefahrstoffe
	GHS01	Gefahr oder Achtung / Danger or Attention	Explosive Stoffe/Gemische und Erzeugnisse mit Explosivstoff, selbsterzetzliche Stoffe/Gemische, organische Peroxide / Explosive substances / mixtures and products containing explosives, self-reactive substances / mixtures, organic peroxides	- 591
	GHS02	Gefahr oder Achtung / Danger or Attention	Selbsterzetzliche Stoffe/Gemische, organische Peroxide, entzündbare Gase, Aerosole Flüssigkeiten, Feststoffe, selbsterhitzungsfähige Gemische, pyrophore Flüssigkeiten und Feststoffe, Stoffe/Gemische, die bei Berührung mit Wasser entzündbare Gase bilden / Self-reactive substances / mixtures, organic peroxides, flammable gases, aerosols, liquids, solids, self-heating mixtures, pyrophoric liquids and solids, substances / mixtures which form flammable gases on contact with water	- 592
	GHS03	Gefahr oder Achtung / Danger or Attention	Oxidierende Gase, Flüssigkeiten, Feststoffe / Oxidizing gases, liquids, solids	- 593
	GHS04	Achtung / Attention	Verdichtete, verflüssigte, gelöste und tiefgekühlte verflüssigte Gase / Compressed, liquefied, dissolved and refrigerated liquefied gases	- 594
	GHS05	Gefahr oder Achtung / Danger or Attention	Verätzung der Haut, schwere Augenschäden, auch metallkorrosive Eigenschaften / Chemical burns to the skin, severe eye damage, also metal-corrosive properties	- 595
	GHS06	Gefahr / Danger	Äußerst schwere und schwere akute Gesundheitsschäden oder Tod / Extremely severe and severe acute damage to health or death	- 596
	GHS07	Achtung / Attention	Akute Gesundheitsschäden, Reizung der Haut, der Augen und der Atemwege, Sensibilisierung der Haut, narkotisierende Wirkungen / Acute damage to health, irritation of the skin, eyes and the respiratory tract, sensitization of the skin, narcotic effects	- 597
	GHS08	Gefahr oder Achtung / Danger or Attention	Chronische Gesundheitsschäden (Organschädigungen) bei einmaliger oder mehrmaliger Exposition, krebserzeugende, erbgutverändernde und fort-pflanzungsgefährdende Wirkungen, Lungenschäden durch Eindringen von Substanzen in die Lunge (Aspirationsgefahr), Sensibilisierung der Atemwege / Chronic damage to health (damage to organs) after single or multiple exposure, carcinogenic, mutagenic and reproductive effects, lung damage due to the penetration of substances into the lungs (risk of aspiration), sensitization of the respiratory tract	- 598
	GHS09	Achtung oder ohne Signalwort/ Attention or without wording	Giftig für Wasserorganismen mit kurz- und langfristiger Wirkung / Toxic to aquatic organisms with short and long-term effects	- 599

\* 07:00 - 17:00 Uhr, außerhalb dieses Zeitraums kann die Nummer auf dem Sicherheitsdatenblatt angerufen werden / 07:00 am - 05:00 pm, outside this time, the number on the safety data sheet can be called

Für alle anderen Informationen siehe Original-Sicherheitsdatenblatt / For all other information, see the original safety data sheet



电话 (Tel): 0571 8352 7220  
传真 (Fax): 0571 8352 7219  
邮编 (Post code): 311215  
地址 (Add.): 中国杭州市萧山区建设三路 398 号

杭州海关技术中心  
国家危险化学品检测重点实验室 (杭州)

正本/ORIGIN

编号: TCH25027990  
No: TCH25027990  
日期: 2025-09-23  
Date: 2025-09-23

ZAIQ-RF(HH)-01-19

# Safety Data Sheet

扫描查看在线报告



**Applicant name:** Zhejiang Oulun Electric Co., Ltd.

**Product name:** Rechargeable Lithium ion battery JWA210310 / 10.8V 15.6Ah  
168.48Wh

**Date of issue:** 2025-09-23

**Edit institution:** Technology Center of Hangzhou Customs District

**Approver:**

万晓峰

**Note:** 1. Unless otherwise stated, this test report is only responsible for the sample(s).  
2. This test report can not be reproduced, except in full, without prior written permission of the lab.



电话 (Tel): 0571 8352 7220  
传真 (Fax): 0571 8352 7219  
邮编 (Post code): 311215  
地址 (Add.): 中国杭州市萧山区建设三路 398 号

# 杭州海关技术中心

## 国家危险化学品检测重点实验室 (杭州)

正本/ORIGIN

编号: TCH25027990  
No: TCH25027990  
日期: 2025-09-23  
Date: 2025-09-23

ZAIQ-RF(HH)-01-19

## 声 明

### DECLARATION

1. 本报告中检测结果仅对样品负责。

The result in this test report is only valid for the tested samples.

2. 本报告无授权人签字、未加盖本机构报告专用章无效。

This report is invalid without authorized signature or the stamp of this organization.

3. 对本报告中检测数据如有异议, 请在收到报告后十五天内提出复测申请 (部分特殊项目不能复测)。复测以原样为准, 复测维持原结论时, 由申请方承担复测费。

If there is any dissidence to the test data, the entrusting party shall apply for retesting within 15 days upon receiving this report (Some special item can not be retested). The former tested samples will be used as the retested ones. If the retest results are the same as the former ones, the retest fee will be paid by the entrusting party.

4. 本报告各页均为报告不可分割部分, 使用者部分使用检测报告而导致误解或由此造成后果, 本机构不承担任何责任。

This report shall be used in integrity. This organization will not be responsible for any misleading caused by the content of this report.

**1. Identification of substance**

Product Name	Rechargeable Lithium ion battery JWA210310 / 10.8V 15.6Ah 168.48Wh
Other Name	None
Chemical Name	None
Recommended Use	Provide DC power supply for compressor refrigerator (for both home and car use)
Manufacturer	Zhejiang Oulun Electric Co., Ltd.
Address	Building 1-8, No. 22 Hengyi Street, Tangqi Town, Linping District, Hangzhou City, Zhejiang Province / 311101
Supplier	Zhejiang Oulun Electric Co., Ltd.
Address	Building 1-8, No. 22 Hengyi Street, Tangqi Town, Linping District, Hangzhou City, Zhejiang Province / 311101
Phone Number	+86-0571-8616 3903
Fax Number	None
WEB or E-mail	None
Emergency Phone Number	+86-0571-8616 3903 or Call your nearest poison control centre

**2. Hazards identification**

GHS classification	The product meets the definition of "article". In the Globally Harmonized system of Classification and Labeling of Chemicals (GHS), the "articles" defined by the US Occupational Safety and Health Administration "Hazard Communication Standard" (29 CFR 1910.1200) or similar definitions do not fall within the scope of this system. [Rev. 10 (2023) Part 1.3.2.1.1]. According to GHS system (10th revised edition), not classified as a hazardous chemical.
GHS Pictograms	—
Signal words	—
Hazard statements	—
Precautionary Statement	—
Prevention	—
Precautionary Statement	—
Response	—
Precautionary Statement	—
Storage	—
Precautionary Statement	—
Disposal	—
Other hazards which do not result in classification	Not available.

**3. Composition/information on ingredients** **Substances** **Mixtures****Component Information**

Component	CAS number	EINECS number	Mass(%wt)
Cobalt lithium manganese nickel oxide	182442-95-1	695-690-9	36.30
Iron	7439-89-6	231-096-4	27.00
Graphite	7782-42-5	231-955-3	19.70
Copper	7440-50-8	231-159-6	7.90
Aluminum	7429-90-5	231-072-3	3.50
Polyethylene	9002-88-4	618-339-3	1.8
Lithium	21324-40-3	244-334-7	1.3
Hexafluorophosphate			
Polyvinylidene Fluoride(PVDF)	24937-79-9	607-458-6	1.30
Carbon Black	1333-86-4	215-609-9	1.20

Note:1. Unless a component presents a severe hazard, it does not need to be considered in the SDS if the concentration is less than 1%.

#### 4. First-aid measures

NOTE TO PHYSICIAN	In case of shortness of breath, give oxygen. Keep victim warm. Keep victim under observation.
After inhalation	Move to fresh air. Oxygen or artificial respiration if needed. Get immediate medical attention.
After skin contact	In case of contact with substances in the battery, immediately flush skin thoroughly with soap and plenty of water. Remove and isolate contaminated clothing and shoes. If irritation persists, get medical attention immediately. For minor skin contact, avoid spreading material on unaffected skin. Wash clothing separately before reuse.
After eye contact	In case of contact with substances in the battery, immediately flush eyes with plenty of water for at least 15 minutes. Assure adequate flushing of the eyes by separating the eyelids with fingers. Get medical attention immediately.
After ingestion	Rinse mouth. Do not induce vomiting without medical advice. If vomiting occurs naturally, have victim lean forward to reduce risk of aspiration. Loosen tight clothing such as a collar, tie, belt or waistband. Do not use mouth-to-mouth method if victim ingested the substance. Seek immediate medical attention.
Most important symptoms / effects, acute and delayed	The battery's electrolyte can irritate skin, eyes, and mucosal tissues.

#### 5. Fire-fighting measures

Suitable extinguishing agents	Water (cooling), use a HFC (hydrofluorocarbon) clean-agent fire extinguisher or alcohol resistant foam fire extinguishers. Heptafluoropropane and perfluorohexanone have better extinguishing effects.
-------------------------------	--

Special hazards caused by the material, its products of combustion or flue gases	Cell may vent when subjected to excessive heat-exposing battery contents. Can be released in case of fire: carbon monoxide, carbon dioxide, nitrogen oxides, hydrogen fluoride, hydrogen cyanide, benzene, toluene, methane, lithium oxide fumes, phosphorus oxides, irritating and toxic fumes and gases.
Protective equipment for fire-fighters	Wear full protective clothing, including helmet, self-contained positive pressure or pressure demand breathing apparatus, protective clothing and face mask, insulating gloves, insulating boots, etc.
<b>6. Accidental release measures</b>	
Person-related safety precautions	If the battery material is released, remove personnel from area until fumes dissipate. Provide maximum ventilation to clear out hazardous gases. Avoid skin and eye contact or inhalation of vapors.
Measures for environmental protection	Prevent further leakage or spillage if safe to do so. Do not allow material to be released to the environment without proper governmental permits.
Measures for cleaning/collecting	If batteries show signs of leaking, avoid skin or eye contact with the material leaking from the battery. Use chemical resistant rubber gloves and non-flammable absorbent materials for clean up. Mix with inert material (e.g. dry sand, vermiculite) and transfer to sealed container for disposal.
Additional information	See Section 7 for information on safe handling See section 8 for information on personal protection equipment. See Section 13 for information on disposal.

**7. Handling and storage****Handling****Information for safe handling**

Operators should be trained and strictly abide by the operating procedures. It is recommended that operators wear general protective clothing and safety gloves. Keep away from fire, heat source and direct sunlight. Smoking is strictly prohibited in the workplace. Provide ventilation systems and equipment in the workplace. Such batteries must be packed in inner packages in such a manner as to effectively prevent short circuits and to prevent movement which could lead to short circuits. Avoid mechanical or electrical abuse. More than a momentary short circuit will generally reduce the battery service life. Avoid reversing battery polarity within the battery assembly. In case of a battery unintentionally be crushed, rubber gloves must be used to handle all battery components. Avoid contact with eyes, skin. Avoid inhalation. Store separately from strong oxidizing agents, corrosives.

Information about protection against explosions and fires	Avoid mechanical and electrical abuse. Do not short circuit or install incorrectly. Batteries may explode or cause burns if disassembled, crushed, recharged or exposed to high temperatures. Install batteries in accordance with equipment instructions.
Requirements to be met by storerooms and containers	Prohibit physical or electrical abuse, prohibit high-temperature storage. Storage preferably in cool, dry and ventilated area, which is subject to little temperature change. Do not place the battery near heating equipment, nor expose to direct sunlight for long periods.
Information about storage in one common storage facility	Store in a cool, well-ventilated and dry area. Keep away from fire, heat source and direct sunlight. Such batteries must be packed in inner packages in such a manner as to effectively prevent short circuits and to prevent movement which could lead to short circuits. Materials to Avoid: strong oxidizing agents, flammables, explosive material, corrosives, harmful substances.
Further information about storage conditions	The storage area shall be equipped with corresponding types and quantities of fire-fighting equipment, leakage emergency treatment equipment and appropriate materials.

#### 8. Exposure controls/personal protection

##### Limit Values for Exposure

Component	CAS number	ACGIH TLV-TWA mg/m <sup>3</sup>	ACGIH TLV-STEL mg/m <sup>3</sup>	NIOSH REL-TWA mg/m <sup>3</sup>	NIOSH REL-STEL mg/m <sup>3</sup>
Cobalt lithium manganese nickel oxide	182442-95-1	N.E.	N.E.	N.E.	N.E.
Iron	7439-89-6	N.E.	N.E.	N.E.	N.E.
Graphite	7782-42-5	2	N.E.	2.5	N.E.
Copper	7440-50-8	0.2	N.E.	1	N.E.
Aluminum	7429-90-5	1	N.E.	10 (total) 5 (resp)	N.E.
Polyethylene	9002-88-4	N.E.	N.E.	N.E.	N.E.
Lithium Hexafluorophosphate	21324-40-3	N.E.	N.E.	N.E.	N.E.
Polyvinylidene Fluoride(PVDF)	24937-79-9	N.E.	N.E.	N.E.	N.E.
Carbon Black	1333-86-4	3	N.E.	3.5	N.E.
Appropriate engineering controls	Use ventilation system and equipment. In case of battery venting, provide as much ventilation as possible. Avoid confined areas with venting cell cores. Provide safety shower and eye wash equipment.				

General protective and hygienic measures	Not necessary under conditions of normal use. Personal protection is recommended for venting battery. No smoking, drinking and eating at working site. Wash thoroughly after handling.
Personal protective equipment	Personal protection is recommended for venting battery: respiratory protection, protective gloves, protective clothing and safety glass with side shields.
Breathing equipment	When workers are facing high concentrations they must use appropriate certified respirators. Respiratory protection is not necessary under conditions of normal use.
Protection of hands	Not necessary under conditions of normal use.
Eye/Face protection	Not necessary under conditions of normal use. Use safety glasses with side shields or safety goggles as mechanical barrier for prolonged exposure if necessary.
Body protection	Not necessary under conditions of normal use. Full set of anti chemical reagent overalls, flame retardant antistatic protective clothing if necessary, choose body protection according to the amount and concentration of the dangerous substance at the work place.

Note: 1. N.E. means not established.

#### 9. Physical and chemical properties

Physical state	Rechargeable Lithium ion battery, with a black prismatic appearance. Size (L*W*H), 134*90*80 (mm) Weight, 1161.77g
Colour	See physical state
Odour	Odourless
Melting point/freezing point	No data available
Boiling point or initial boiling point and boiling range	No data available
Flammability	No data available
Lower and upper explosion limit/flammability limit	No data available
Flash point	No data available
Auto-ignition temperature	No data available
Decomposition temperature	No data available
pH	No data available
Kinematic viscosity	No data available
Solubility	No data available

Partition coefficient: n-octanol/water (log value)	No data available
Vapour pressure	No data available
Density and/or relative density (water=1)	No data available
Relative vapour density (air=1)	No data available
Particle characteristics	No data available

#### 10. Stability and reactivity

Reactivity	No data available.
Chemical stability	This is a stable product under recommended storage conditions.
Possibility of hazardous reactions	No polymerization.
Conditions to avoid (e.g. static discharge, shock or vibration)	Fire source, heating source, disassemble, external short circuit, crushes, deformation, high temperature, direct sunlight, high humidity, immerse in water or overcharge, etc.
Incompatible materials	Explosives, flammables, strong oxidants and corrosives. If leaked, forbidden to contact with strong oxidizing agents, mineral acids, strong alkalis, etc.
Hazardous decomposition products	May include metal oxides, carbon monoxide, carbon dioxide, nitrogen oxides, hydrogen fluoride, hydrogen cyanide, benzene, toluene, methane, phosphorus oxides and other toxic smoke and gas.

#### 11. Toxicological information

Routes of Entry: Dermal contact, eye contact, inhalation, ingestion.	
Acute Toxicity	LD50 (Oral, rat) N/A LC50 (Inhalation, rat) N/A LD50 (Dermal, rabbit) N/A
Skin corrosion/Irritation	The electrolyte may cause skin irritation.
Serious eye damage/irritation	The electrolyte may cause eye irritation.
Respiratory or skin sensitization	Not classified
Germ cell mutagenicity	Not classified
Carcinogenicity	Not classified
Reproductive toxicity	Not classified
STOT-single exposure	Not classified
STOT-repeated exposure	Not classified
Aspiration hazard	Not classified
Chronic Effects	Not classified
Further Information	In the event of exposure to internal contents, moderate or severe irritation, burning and dryness of the skin may occur,

and may damage the nerves of the target organs.  
No detailed toxicological study.

## 12. Ecological information

### Ecotoxicity

#### Aquatic Toxicity

##### Test & Species

96 Hr LC50 fish: N/A

48 Hr EC50 Daphnia: N/A

72 Hr EC50 Algae: N/A

### Persistence and degradability

Not available

### Bioaccumulative potential

Not available

### Mobility in soil

Not available

### Additional Information

May cause water or soil pollution.

## 13. Disposal considerations

### WASTE DISPOSAL INSTRUCTIONS

Contact a qualified professional waste disposal service to dispose of this material.

Dispose of in accordance with local environmental regulations or local authority requirements.

## 14. Transport information

### The Recommendation of Transport of Dangerous Goods (TDG)

UN Number UN 3480

Proper Shipping Name LITHIUM ION BATTERIES

Class/Division Class 9 Miscellaneous Dangerous Substances and Articles

Package Group —

Subsidiary risk —

labeling pictogram



Note: The sample is a rechargeable Lithium-ion Battery Pack with a Watt-hour rating in excess of 100wh, which contains 18 cells in 6 parallels and 3 strings, and passed the tests required by UN 38.3. Cells and batteries incorporate a safety venting device. Cells and batteries are properly protected to prevent short circuits and reverse currents, and have a high quality management programme can be transported as mentioned above. Cells or batteries shall be packed in packagings so that the cells or batteries are protected against damage that may be caused by the movement or placement of the cells or batteries within the packaging. The completed package must meet the Packing Group II performance requirements.

Each package must be labeled with the Class 9 Lithium Battery hazard label (Model No.9A ,5.2.2.2.2 in TDG) .

According to 2.9.4 (g) of TDG (23rd revised edition.), except for button cells installed in equipment (including circuit boards), manufacturers and subsequent distributors of cells or batteries manufactured after 30 June 2003 shall make available the test summary as specified in the Manual of Tests and Criteria, Part III, sub-section 38.3, paragraph 38.3.5.

Maritime transport IMDG	Being same with TDG Marine pollutant (Yes/No): No EmS No.: F-A, S-I Each package must be labeled with the Class 9 Lithium Battery hazard label (Model No.9A ,5.2.2.2.2 in IMDG code). According to 2.9.4.7 of IMDG Code (2022 Edition), except for button cells installed in equipment (including circuit boards), manufacturers and subsequent distributors of cells or batteries manufactured after 30 June 2003 shall make available the test summary as specified in the Manual of Tests and Criteria, Part III, sub-section 38.3, paragraph 38.3.5.
-------------------------	--

## 15. Regulatory information

### European/International Regulations

<b>OSHA:</b>	Hazardous by definition of Hazard Communication Standard (29CFR 1910.1200).
<b>EINECS Status:</b>	The main components (except Cobalt lithium manganese nickel oxide, Polyethylene, Polyvinylidene Fluoride (PVDF)) of this chemical are included in EINECS inventory.
<b>EPA TSCA Status:</b>	The main components of this chemical are included in TSCA inventory.
<b>Canadian DSL/NDSL (Domestic Substances List/ Non-domestic Substances List):</b>	The main components (except Cobalt lithium manganese nickel oxide) of this chemical are included in DSL / NDSL.
<b>HMIS (Hazardous Material Identification System Ratings):</b>	Health: 1 Flammability: 0 Physical hazard: 0 Personal protection: F (4. Severe Hazard; 3. Serious Hazard; 2. Moderate Hazard; 1. Slight Hazard; 0. Minimal Hazard)
<b>WHMIS (Canadian Workplace Hazardous Material Identification System Ratings):</b>	B4, D2B (Iron), B4, D2A (Carbon Black), B4, D2B (Copper), B6 (Aluminum), D1A, D2B, E (Lithium Hexafluorophosphate).
<b>List of dangerous goods (GB</b>	UN Number: UN3480, Shipping Name: LITHIUM ION BATTERIES, Packing Group: II.

**12268-2012)****16. other information**

Employers should use this information only as a supplement to other information gathered by them, and should make independent judgement of suitability of this information to ensure proper use and protect the health and safety of employees. This information is furnished without warranty, and any use of the product not in conformance with this Material Safety Data Sheet, or in combination with any other product or process, is the responsibility of the user.

This Material Safety Data Sheet was based on the "Globally Harmonized System of Classification and Labelling of Chemicals", Recommendations on the TRANSPORT OF DANGEROUS GOODS Model Regulations", "International Maritime Dangerous Goods Code", Dangerous Goods Regulations by the "International Air Transport Association", the National Standards and other related dangerous chemicals management laws, regulations and standards, which are periodically updated and changed. To make dangerous goods / hazardous chemicals comply with the relevant requirements of the latest management, regularly update is recommended.

This Material Safety Data Sheet has been compiled in both English and Chinese. For any discrepancies, the Chinese version shall prevail.

<b>Abbreviations and acronyms</b>	TDG: The Recommendation of Transport of Dangerous Goods ADR: Agreement Concerning the International Carriage of Dangerous Goods by Road RID: Regulation Concerning the International Carriage of Dangerous Goods by Rail IMDG: International Maritime Dangerous Goods Code IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA) ICAO-TI: Technical Instructions for the Safe Transport of Dangerous Goods by Air by the "International Civil Aviation Organization" (ICAO) EINECS: European Inventory of Existing Commercial Chemical Substances CAS: Chemical Abstracts Service LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent EC50: Effective concentration, 50 percent
<b>Edit Date</b>	23.09.2025
<b>Update and Revise</b>	Original edition
<b>Edit Standard</b>	<i>Globally Harmonized System of Classification and Labelling of Chemicals</i> Part 1.5
<b>Revised Institution</b>	Technology Center of Hangzhou Customs District



电话 (Tel): 0571 8352 7220

传真 (Fax): 0571 8352 7219

邮编 (Post code): 311215

地址 (Add.): 中国杭州市萧山区建设三路 398 号

# 杭州海关技术中心

国家危险化学品检测重点实验室 (杭州)

正本/ORIGIN

编号: TCH25027990

No: TCH25027990

日期: 2025-09-23

Date: 2025-09-23

ZAIQ-RF(HH)-01-19

扫描查看在线报告

## 化学品安全数据表



申请单位: 浙江欧伦电气股份有限公司

产品名称: 可充电锂离子电池 JWA210310 / 10.8V 15.6Ah 168.48Wh

签发日期: 2025-09-23

编制机构: 杭州海关技术中心

批准人:

万晓军

注: 1.除非特别说明, 本报告仅对样品负责。  
2.未经本实验室许可, 本报告不得部分复制。



电话 (Tel): 0571 8352 7220

传真 (Fax): 0571 8352 7219

邮编 (Post code): 311215

地址 (Add.): 中国杭州市萧山区建设三路 398 号

# 杭州海关技术中心

## 国家危险化学品检测重点实验室（杭州）

正本/ORIGIN

编号: TCH25027990

No: TCH25027990

日期: 2025-09-23

Date: 2025-09-23

ZAIQ-RF(HH)-01-19

## 声 明

### DECLARATION

1. 本报告中检测结果仅对样品负责。

The result in this test report is only valid for the tested samples.

2. 本报告无授权人签字、未加盖本机构报告专用章无效。

This report is invalid without authorized signature or the stamp of this organization.

3. 对本报告中检测数据如有异议, 请在收到报告后十五天内提出复测申请(部分特殊项目不能复测)。复测以原样为准, 复测维持原结论时, 由申请方承担复测费。

If there is any dissidence to the test data, the entrusting party shall apply for retesting within 15 days upon receiving this report (Some special item can not be retested). The former tested samples will be used as the retested ones. If the retest results are the same as the former ones, the retest fee will be paid by the entrusting party.

4. 本报告各页均为报告不可分割部分, 使用者部分使用检测报告而导致误解或由此造成后果, 本机构不承担任何责任。

This report shall be used in integrity. This organization will not be responsible for any misleading caused by the content of this report.

1. 标识			
产品名称	可充电锂离子电池 JWA210310 / 10.8V 15.6Ah 168.48Wh		
英文名称	Rechargeable Lithium ion battery JWA210310 / 10.8V 15.6Ah 168.48Wh		
其他名称	无		
化学名称	无		
使用建议	给压缩机电冰箱（车家两用）提供直流电源		
生产商	浙江欧伦电气股份有限公司		
地址	浙江省杭州市临平区塘栖镇恒毅街 22 号 1-8 棚 / 311101		
供应商	浙江欧伦电气股份有限公司		
地址	浙江省杭州市临平区塘栖镇恒毅街 22 号 1-8 棚 / 311101		
固定电话	+86-0571-8616 3903		
传真	无		
网址或电子邮件地址	无		
应急电话	+86-0571-8616 3903 或向离你最近的解毒中心求助		
2. 危险标识			
GHS 危险性分类	该产品符合“物品”的定义。在全球化学品统一分类和标签制度(GHS)中，美国职业安全和健康署“危险公示标准”(29 CFR 1910.1200)或类似定义界定的“物品”不属于这一制度的范围。[Rev. 10 (2023) Part 1.3.2.1.1]。根据 GHS 制度（第十修订版），未被归类为危险化学品。		
GHS 危险标签	—		
信号词	—		
危险说明	—		
防范说明	—		
预防	—		
防范说明	—		
反应	—		
防范说明	—		
贮存	—		
防范说明	—		
处置	—		
不导致分类的其他危险	未知。		
3. 成分构成/成分信息			
□物质			
✓混合物			
成分信息			
成分	<b>CAS 号</b>	<b>EINECS 号</b>	<b>含量(%wt)</b>
钴锂锰镍的氧化物	182442-95-1	695-690-9	36.30
铁	7439-89-6	231-096-4	27.00
石墨	7782-42-5	231-955-3	19.70
铜	7440-50-8	231-159-6	7.90

铝	7429-90-5	231-072-3	3.50
聚乙烯	9002-88-4	618-339-3	1.8
六氟磷酸锂	21324-40-3	244-334-7	1.3
聚偏氟乙烯	24937-79-9	607-458-6	1.30
炭黑	1333-86-4	215-609-9	1.20

注: 1.在化学品安全数据表中无需考虑百分含量小于 1% 的成分, 除非该成分呈现出严重的危害性。

#### 4. 急救措施

对医师的建议	在呼吸急促的情况下, 需给受害人输氧。保持受害人温暖。让受害人处于观察监护下。
吸入后	转移到有新鲜空气的地方。如需要, 须输氧或进行人工呼吸。马上就医。
皮肤接触后	若接触到电池内的物质, 立即用肥皂和大量清水彻底冲洗皮肤。脱掉被污染的衣服和鞋子。如皮肤刺激仍继续: 须求医。如原是小面积的皮肤接触, 防止接触面积的扩大。污染的衣服在使用前, 须单独清洗。
眼睛接触后	若接触到电池内的物质, 立即用大量的水冲洗眼睛至少 15 分钟。用手指分开眼睑以保证充分冲洗眼睛。马上就医。
摄入后	漱口。无医师建议的情况下不要引吐。如果受害人需呕吐, 使其前倾以减少倒吸的危险。解松过紧的衣物, 如领子、领带、皮带或腰带。不要使用嘴对嘴的方法实施救助。马上就医。
主要的症状和影响, 包括急性和迟发效应	电池的电解质会刺激皮肤、眼睛和黏膜组织。

#### 5. 消防措施

合适的灭火剂	大量水 (降温), 可用 HFC (氢氟碳化合物) 清洁剂灭火器或耐醇泡沫灭火器。七氟丙烷和全氟己酮对锂电池灭火效果较好。
由物质本身或其燃烧产物、烟气产生的特殊危险	当电芯暴露于过热的环境中时, 安全阀可能会打开。 在发生火灾时可能释放: 一氧化碳、二氧化碳、氮氧化物、氟化氢、氯化氢、苯、甲苯、甲烷、锂氧化物烟气, 磷氧化物, 刺激性有毒烟雾和气体。
消防人员的特殊防护设备	穿全套防护衣物, 包括头盔, 自给正压式呼吸器, 防护服和面罩, 绝缘手套、绝缘靴等。

#### 6. 泄漏应急处理

与人相关的安全防范措施	如果电池内部材料泄露, 试验人员应立刻撤离试验区直到烟气消散。将通风设备打开吹散危险性气体。避免皮肤和眼睛接触或吸入有害气体。如能做到应防止进一步的泄露和溢出。无相关政府许可, 不允许把该物质释放到环境中。
环境保护措施	如果电池有泄漏迹象, 避免皮肤或眼睛接触电池泄漏的材料。使用耐化学腐蚀的橡胶手套和不易燃的吸收性材料进行清洁。与惰性材料 (如干沙, 蚤石) 混合并转移到密封的容器待处理。
清洁/收集措施	关于安全操作的信息见第 7 部分 关于个人防护设备的信息见第 8 部分 关于处置的信息见第 13 部分
附加说明	

#### 7. 操作和存储

#### 操作

安全操作的信息	操作人员应经过培训, 严格遵守操作规程。建议操作人员穿一般作业防护服, 戴安全手套。远离火种、热源, 避免阳光直射。工作场所严禁吸烟。工作场所应有通风系统和设备。避免随意拆卸电池和弄错正负极。须牢固在内包装中, 以有效防止短路和防止可导致短路的移动。万一电池内的物质泄漏, 避免眼睛、皮肤直接接触, 避免吸入。应与强氧化剂、腐蚀品分开存放。
防止爆炸和火灾的信息	避免机械和电气的滥用。不要短路或安装错误。 电池如果拆卸、压碎、充电或暴露在高温下, 可能会发生爆炸和燃烧。 按照设备说明书安装电池。
<b>存储</b>	
对储藏室和容器的要求	禁止物理或电滥用, 禁止高温储存, 最好将电池储存在阴凉、干燥、通风等温度变化较小的环境中。禁止将电池接触加热设备或将电池直接暴露于阳光中。
关于储藏在普通存储设施中的信息	储存于阴凉、通风、干燥的库房内。远离火种、热源, 避免阳光直射。须牢固在内包装中, 以有效防止短路和防止可导致短路的移动。应与强氧化剂、易燃易爆、腐蚀品、有害物质分开存放。
关于储藏条件进一步的信息	储存区配备相应品种和数量的消防器材、泄漏应急处理设备和合适的收容材料。

## 8. 暴露控制/人身保护

### 暴露限值

成分	CAS 号	ACGIH 阈限值-时间加权平均浓度 mg/m <sup>3</sup>	ACGIH 阈限值-短时间接触限值 mg/m <sup>3</sup>	NIOSH 阈限值-时间加权平均浓度 mg/m <sup>3</sup>	NIOSH 阈限值-短时间接触限值 mg/m <sup>3</sup>
钴锂锰镍的氧化物	182442-95-1	N.E.	N.E.	N.E.	N.E.
铁	7439-89-6	N.E.	N.E.	N.E.	N.E.
石墨	7782-42-5	2	N.E.	2.5	N.E.
铜	7440-50-8	0.2	N.E.	1	N.E.
铝	7429-90-5	1	N.E.	10(总尘) 5(呼尘)	N.E.
聚乙烯	9002-88-4	N.E.	N.E.	N.E.	N.E.
六氟磷酸锂	21324-40-3	N.E.	N.E.	N.E.	N.E.
聚偏氟乙烯	24937-79-9	N.E.	N.E.	N.E.	N.E.
炭黑	1333-86-4	3	N.E.	3.5	N.E.
减少接触的工程控制方法	有通风系统和设备。当电池排气阀打开时, 应尽量使通风设备开至最大, 避免将打开排气阀的电芯局限在某一狭窄空间内。提供安全淋浴和洗眼设备。				
一般保护和卫生措施	正常使用条件下不需要。电池开阀试验时应做好个人防护。工作场所严禁吸烟、饮水和饮食。工作后, 沐浴更衣。				
个人防护用品	电池开阀试验时应做好个人防护, 呼吸防护, 防护手套, 防护服和有护边的安全玻璃罩。				
呼吸设备	当工人在高浓度的环境下工作时, 必须使用合适的已认证的呼吸器。正				

双手保护	常操作条件下，呼吸保护是不必要的。
眼睛/面部保护	正常使用条件下不需要。
身体保护	正常使用条件下不需要。必要时使用带侧罩或安全眼镜的护目镜作为工人长期暴露的机械屏蔽。
	正常使用条件下不需要。必要时穿戴全套防化学试剂工作服，阻燃防静电防护服，防护设备的类型必须根据特定工作场所中的危险物的浓度和含量来选择。

注:1. N.E. — 未建立。

#### 9. 物理和化学特性

物理状态	该样品是可充电锂离子电池，外观为黑色棱柱形。 尺寸（长宽高）：134*90*80 (mm) 重量：1161.77g
颜色	见物理状态
气味	无味
熔点/凝固点	无数据资料
沸点或初始沸点和沸程	无数据资料
易燃性	无数据资料
上、下爆炸极限/易燃极限	无数据资料
闪点	无数据资料
自燃温度	无数据资料
分解温度	无数据资料
pH 值	无数据资料
运动粘度	无数据资料
溶解性	无数据资料
分配系数：正辛醇/水 (对数值)	无数据资料
蒸汽压	无数据资料
密度和/或相对密度 (水=1)	无数据资料
相对蒸气密度 (空气=1)	无数据资料
颗粒特征	无数据资料

#### 10. 稳定性和反应活性

反应性	无数据资料。
化学稳定性	在要求的贮存条件下，这是个稳定的产品。
有害反应的可能性	不聚合。
需避开的条件 (如：静电放电，震动等)	火源、热源、拆卸、外部短路、压碎、变形、高温、阳光直射、高湿度、浸水或过充等。
不相容的物质	爆炸品、易燃物、强氧化剂和腐蚀剂。如果发生泄漏，避免与强氧化剂，无机酸，强碱等接触。
有害分解产物	可能包括金属氧化物，一氧化碳、二氧化碳、氮氧化物、氟化氢、氰化

氢、苯、甲苯、甲烷、磷氧化物等有毒烟雾和气体。

## 11. 毒理学信息

进入人体内的途径：皮肤接触、眼睛接触、吸入和摄入。

急性毒性	LD50 (口服, 大鼠) : 未知
	LC50 (吸入, 大鼠) : 未知
	LD50 (皮肤, 兔子) : 未知
皮肤腐蚀/刺激	其中的电解质对皮肤有刺激性。
严重眼损伤/刺激	其中的电解质对眼睛有刺激性。
呼吸或皮肤敏化作用	未分类
生殖细胞致突变性	未分类
致癌性	未分类
生殖毒性	未分类
特定目标器官毒性-单次接触	未分类
特定目标器官毒性-重复接触	未分类
吸入危险	未分类
慢性影响	未分类
其他信息	万一发生与电芯内部材料接触的事故, 轻微或严重的刺激, 都可能使皮肤出现干燥和灼烧的感觉, 并可能损坏靶器官的神经。无详细的毒理学研究。

## 12. 生态学信息

生态毒性

水生毒性

测试 & 物种

96 Hr LC50 鱼: 未知

48 Hr EC50 滯类: 未知

72 Hr EC50 藻类: 未知

持久性和降解性

未知

潜在的生物累积性

未知

土壤中的迁移性

未知

其他信息

可能造成水或土壤污染。

## 13. 废弃处置

废物处置说明

联系一家有资质的专业废物处置机构来处置。

按照当地的环境法规或地方当局的要求来进行处置。

## 14. 运输信息

联合国《关于危险货物运输的建议书 规章范本》(TDG)

UN 编号

UN 3480

正式运输名称

锂离子电池组

危险类/项别

第 9 类 杂项危险物质和物品

包装类别

—

次要危险性

—

## 危险性标签



注：该样品为可充电锂离子电池组，瓦特-小时额定值大于 100wh，内含 3 串 6 并共 18 个电芯，并通过 UN 38.3 要求的各项试验。该锂电池需装有安全排气、防止外部短路以及防止反向电流造成危险所需的有效装置，并有高质量的管理方案才可按上述条目运输。装在包装中的锂电池，应采取保护措施，防止锂电池因在包装中的移动或位置变化而造成损坏。包装件必须满足 II 级包装的性能要求。

每个包装件必须使用 9 类锂电池危险性标签 (TDG 5.2.2.2.2 图 No.9A)。

根据 TDG (第 23 修订版) 的 2.9.4 (g)，除了安装在设备 (包括电路板) 上的纽扣电池外，2003 年 06 月 30 日以后制造的锂电池或电池组的制造商和出厂后的销售商应提供联合国《试验和标准手册》第 III 部分第 38.3 小节第 38.3.5 段规定的 UN38.3 试验概要。

## 国际海运危规 IMDG

与 TDG 的分类相同

海洋污染物 (是/否)：否

EmS 编号：F-A, S-I

每个包装件必须使用 9 类锂电池危险性标签 (IMDG code 5.2.2.2.2 图 No.9A)。

根据 IMDG Code(2022 版)的 2.9.4.7，除了安装在设备 (包括电路板) 中的纽扣电池，2003 年 06 月 30 日之后生产的锂电池或电池组的制造商和出厂后的销售商应提供联合国《试验和标准手册》第 III 部分第 38.3 小节第 38.3.5 段规定的 UN38.3 试验概要。

## 15. 法规信息

## 欧洲/国际法规

**OSHA (美国职业安全和健康管理法):**

危险性根据危害通讯标准来编写 (29CFR 1910.1200)。

**EINECS (欧洲现有商业化学物质名录):**

该样品各主要成分 (除钴锂锰镍的氧化物、聚乙烯和聚偏氟乙烯之外) 已被列入 EINECS 目录中。

**EPA TSCA (有毒物质控制法):**

该样品各主要成分已被列入 TSCA 目录中。

**加拿大 DSL/NDSL (国内物质清单)/ (非国内物质清单):**

该样品各主要成分 (除钴锂锰镍的氧化物之外) 已被列入 DSL/NDSL 目录中。

**HMIS (危险品识别系统):**

健康危害：1

易燃性：0

物理危害：0

个人防护：F

(4. 极其严重危害；3. 严重危害；2. 中度危害；1. 轻度危害；0. 极小危害)

**WHMIS (加拿大工**

B4、D2B (铁)，B4、D2A (炭黑)，B4、D2B (铜)，B6 (铝)，

工作场所所有害物质识别 D1A、D2B、E (六氟磷酸锂)。

系统):

危险货物品名表 (GB 联合国编号: UN 3480, 名称和说明: 锂离子电池组, 包装类别: II。  
**12268-2012**)

## 16. 其他信息

雇主只能把本化学品安全数据表的信息当作他们所获其他信息的补充信息, 并能独立判断此信息的适用性, 以确保正确使用并保护雇员的健康和安全。此化学品安全数据表提供的信息并不具担保作用, 任何未按本化学品安全数据表使用产品、或与其他产品和操作过程同时使用本产品时产生的后果由用户自行承担。

本化学品安全数据表是根据《全球化学品统一分类和标签制度》, 联合国《关于危险货物运输的建议书》, 《国际海运危险货物规则》, 国际航空运输协会《危险货物规则》和国家标准等相关危险化学品管理法律法规和标准进行编制, 而上述法律法规和标准均会定期进行更新和变化。为使危险货物/危险化学品符合相关最新的管理要求, 建议定期审核更新化学品安全数据表。

本化学品安全数据表分别以中、英文编制, 在对中、英文本的理解上发生歧义时, 以中文文本为准。

缩略语	TDG: 联合国《关于危险货物运输的建议书 规章范本》 ADR: 《国际危险货物公路运输协定》 RID: 《国际危险货物铁路运输规则》 IMDG: 国际海事组织《国际海运危险货物规则》 IATA-DGR: 国际航空运输协会《危险货物规则》(IATA) ICAO-TI: 国际民用航空组织《危险物品安全航空运输技术细则》(ICAO) EINECS: 欧洲现有商业化学物质名录 CAS: 化学文摘号 LC50: 半数致死浓度 LD50: 半数致死剂量 EC50: 半数效应浓度
编制日期	2025.09.23
更新和修改	第 1 版
编制标准	全球化学品统一分类和标签制度 第 1.5 部分
编制机构	杭州海关技术中心

样品照片 Sample Photos
内部电芯/Inner Cell(INR18650P/3.6V 2.6Ah 9.36Wh)
电池/Battery(JWA210310 / 10.8V 15.6Ah 168.48Wh)
铭牌/Nameplate
委托方提供的包装照片 / Package Photos provided by the Applicant

\*\*\*报告结束\*\*\*



# R- 600a Material Safety Data Sheet

## 1 PRODUCT AND COMPANY IDENTIFICATION

Product Name	Isobutane;2-methylpropane;R600a
Product Synonym(s)	A list of applicable products can be found in Section 16
Chemical Family	2-methylpropane
Chemical Formula	C4H10
Chemical Name	2-METHYLPROPANE(R600a)
EPA Reg Num	
Product Use	Refrigerant

### Company Identification

#### Quzhou Xiecheng Chemical Co., Ltd.

Add: Room 601-1, Building10, Shiji Tiancheng District, Quzhou, Zhejiang, China (Mainland)

### PHONE NUMBERS

Product Information : 86-570-8086170  
Transport Emergency : 86-570-8086572  
Medical Emergency : 86-570-8086572

## 2 COMPOSITION / INFORMATION ON INGREDIENTS

Ingredient Name	CAS RegistryNumber	Typical Wt. %	OSHA
2-Methylpropane(R600a)	75-28-5	100%	Y

The substance(s) marked with a "Y" in the OSHA column, are identified as hazardous chemicals according to the criteria of the OSHA Communication Standard (29 CFR 1910.1200)

This material is classified as hazardous under Federal OSHA regulation.

The components of this product are all on the TSCA inventory list.

## 3 HAZARDS IDENTIFICATION

### Emergency Overview

Clear, colorless liquified gas with faint ethereal (ether like) odor.

### WARNING!

LIQUID AND GAS UNDER PRESSURE, OVERHEATING AND OVERPRESSURIZING MAY CAUSE GAS RELEASE OR VIOLENT CYLINDER BURSTING. MAY DECOMPOSE ON CONTACT WITH FLAMES OR EXTREMELY HOT METAL SURFACES TO PRODUCE TOXIC AND CORROSIVE PRODUCTS. VAPOR REDUCES OXYGEN AVAILABLE FOR BREATHING AND IS HEAVIER THAN AIR. HARMFUL IF INHALED AND MAY CAUSE HEART IRREGULARITIES, UNCONSCIOUSNESS OR DEATH. LIQUID CONTACT WITH EYES OR SKIN MAY CAUSE FROSTBITE.

### Potential Health Effects

Inhalation and skin contact are expected to be the primary routes of occupational exposure to this material. As with most liquified gases, contact with the rapidly volatilizing liquid or cold vapor can cause frostbite to any tissue. Highvapor concentrations are irritating to the eyes and respiratory tract and may result in central nervous system (CNS)effects such as headache, dizziness, anesthesia,

drowsiness and, in severe exposure, loss of consciousness and death. The dense vapor of this material may reduce the available oxygen for breathing and produce symptoms such as headache, dizziness, drowsiness, cyanosis and lack of muscle control followed by collapse. Prolonged exposure to an oxygen-deficient atmosphere may be fatal. Inhalation of this material may cause an increase in the sensitivity of the heart to adrenaline, which could result in irregular or rapid heartbeats and reduced heart function. Workers with heart disease or compromised heart function should limit exposure to this material.

#### **4 FIRST AID MEASURES**

IF IN EYES, immediately flush with plenty of water. Get medical attention if irritation persists.  
IF ON SKIN, Flush exposed skin with lukewarm water (not hot), or use other means to warm skin slowly. Get medical attention if frostbitten by liquid or if irritation occurs.  
IF SWALLOWED, Not applicable - product is a gas at ambient temperatures.  
IF INHALED, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention. Do not give adrenaline, epinephrin or similar drugs following exposure to this product.

#### **5 FIRE FIGHTING MEASURES**

##### **Fire and Explosive Properties**

Auto-Ignition Temperature	460 C (3.65 bar)	
Flash Point	NA - GAS	Flash Point Method
Flammable Limits- Upper	NA	
Lower	NA	

##### **Extinguishing Media**

Use extinguishing media appropriate to surrounding fire conditions.

##### **Fire Fighting Instructions**

Stop the flow of gas if possible. Use water spray on person making shut-off. Fire fighters and others who maybe exposed to products of combustion should wear full fire fighting turn out gear (full Bunker Gear) and self-contained breathing apparatus (pressure demand NIOSH approved or equivalent). Fire fighting equipments should be thoroughly decontaminated after use.

##### **Fire and Explosion Hazards**

May decompose on contact with flames or extremely hot metal surfaces to produce toxic and corrosive products. Liquid and gas under pressure, overheating or overpressurizing may cause gas release and/or violent cylinder bursting. Container may explode if heated due to resulting pressure rise. Some mixtures of HCFCs and/or HFCs, and air or oxygen may be combustible if pressurized and exposed to extreme heat or flame.

#### **6 ACCIDENTAL RELEASE MEASURES**

##### **In Case of Spill or Leak**

Use Halogen leak detector or other suitable means to locate leaks or check atmosphere. Keep upwind. Evacuate enclosed spaces and disperse gas with floor-level forced-air ventilation. Exhaust vapors outdoors. Do not smoke or operate internal combustion engines. Remove flames and heating elements.

## 7 HANDLING AND STORAGE

### Handling

Avoid breathing gas. Avoid contact with eyes, skin and clothing. Keep container closed. Use only withadequate ventilation. Do not enter confined spaces unless adequately ventilated.

### Storage

Do not apply direct flame to cylinder. Do not store cylinder in direct sun or expose it to heat above 120 F. Do not drop or refill this cylinder. Keep away from heat, sparks and flames.

## 8 EXPOSURE CONTROLS / PERSONAL PROTECTION

### Engineering Controls

Investigate engineering techniques to reduce exposures below airborne exposure limits. Provide ventilation if necessary to control exposure levels below airborne exposure limits (see below). If practical, use localmechanical exhaust ventilation at sources of air contamination such as open process equipment.

### Eye / Face Protection

Where there is potential for eye contact, wear chemical goggles and have eye flushing equipment available.

### Skin Protection

Wear appropriate chemical resistant protective clothing and chemical resistant gloves to prevent skin contact.Consult glove manufacturer to determine appropriate type glove material for given application. Rinse contaminated skin promptly. Wash contaminated clothing and clean protective equipment before reuse. Wash skin thoroughly after handling.

### Respiratory Protection

Avoid breathing gas. When airborne exposure limits are exceeded (see below), use NIOSH approvedrespiratory protection equipment appropriate to the material and/or its components (full facepiececerecommended). Consult respirator manufacturer to determine appropriate type equipment for a givenapplication. Observe respirator use limitations specified by NIOSH or the manufacturer. For emergency andother conditions where exposure limit may be significantly exceeded, use an approved full face positive-pressure, self-contained breathing apparatus or positive-pressure airline with auxiliary self-contained air supply.

Respiratory protection programs must comply with 29 CFR § 1910.134.

### Airborne Exposure Guidelines for Ingredients

Exposure Limit	Value
2-Methylpoane (R600a)	
WEEL TWA	1000 ppm 4240 mg/m <sup>3</sup>

-Only those components with exposure limits are printed in this section.

-Skin contact limits designated with a "Y" above have skin contact effect. Air sampling alone is insufficient to accurately quantitate exposure. Measures to prevent significant cutaneous absorption may be required.

-ACGIH Sensitizer designator with a value of "Y" above means that exposure to this material may cause allergic reactions.

-WEEL-AIHA Sensitizer designator with a value of "Y" above means that exposure to this material may cause allergic skin reactions.

## 9 PHYSICAL AND CHEMICAL PROPERTIES

Appearance/Odor	Clear, colorless liquified gas with faint etheral (ether like) odor.
pH	NA
Specific Gravity	1.25 @ 4 C
Vapor Pressure	0.765 MPa (3.66 bar) (25 C)
Vapor Density	3.65
Melting Point	NE
Freezing Point	-160 C (-256 F)
Boiling Point	-71.5 C/ -96.7F
Solubility In Water	(25 C): 0.7 g/lMolecular Weight 112.03
Bulk Density	1.25 @ 25 C (g/cm3)
n-Octanol/Water Partition Coefficient	log Pow: 1.16
Other Physical Data	Decomposition temperature: >370 C (700 F) Critical temperature: 160 C Critical pressure: 3..65 MPa (36.5 bar)

## 10 STABILITY AND REACTIVITY

### Stability

This material is chemically stable under specified conditions or storage, shipment and/or use. See HANDLING AND STORAGE section of this MSDS for specified conditions.

### Incompatibility

Avoid contact with strong alkalis or alkaline earth metals, finely powdered metals such as aluminum, magnesium or zinc and strong oxidizers, since they may react or accelerate decomposition.

### Hazardous Decomposition Products

Thermal decomposition products include hydrogen fluoride, hydrogen chloride, carbon monoxide, carbon dioxide and chlorine.

## 11 TOXICOLOGICAL INFORMATION

### Toxicological Information

#### 2-Methylpropane(R600a)

No skin allergy was observed in guinea pigs following repeated exposure. Acute inhalation exposure produced anesthetic effects in mice, dogs, cats and monkeys. Repeated inhalation exposure produced no adverse effects in rats. Inhalation of this material, followed by intravenous injection of epinephrine to simulate stress reactions, resulted in cardiac sensitization in dogs. Following long-term inhalation studies in rats, an increased incidence of benign tumors (at high concentrations) in the testes were the only tumors observed. No birth defects were noted in the offspring of rats exposed to this material by inhalation during pregnancy, even at doses which produced significant adverse effects in the mother. This material produced no genetic changes in standard tests using bacterial or animal cells and whole animals. Single exposure (acute) studies indicate: Inhalation - Practically Non-toxic to Rats (4-hr LC50 >500,000 ppm; 30-min LC50 ~750,000 ppm)

Eye Irritation - Slightly Irritating to Rabbits Skin Irritation - Slightly Irritating to Rabbits (24-hr

exposure)

## 12 ECOLOGICAL INFORMATION

### Ecotoxicological Information

Based on its low n-octanol/water partition coefficient (log Pow of 1.06), bioaccumulation of this material is considered unlikely.

### Chemical Fate Information

Based on its low n-octanol/water partition coefficient (log Pow 1.06), bioaccumulation of this material is considered unlikely. When evaluated in a 28 day activated sludge test, 3% degradation of this material was observed.

## 13 DISPOSAL CONSIDERATIONS

### Waste Disposal

Recover, reclaim or recycle when practical. Dispose of in accordance with federal, state and local regulations. Note: Chemical additions to, processing of, or otherwise altering this material may make this waste management information incomplete, inaccurate, or otherwise inappropriate. Furthermore, state and local waste disposal requirements may be more restrictive or otherwise different from federal laws and regulations.

## 14 TRANSPORT INFORMATION

IMO Name	2-Methylpropane(R600a)
IMO Technical Name	
IMO Hazard Class	2.5
UN Number	UN 3259
IMO Packing Group	PG NA
RQ	

## 15 REGULATORY INFORMATION

### Hazard Categories Under Criteria of SARA Title III Rules (40 CFR Part 370)

Immediate (Acute) Health	Y	Fire	N
Delayed (Chronic) Health	N	Reactive	N
		Sudden Release of Pressure	Y

The components of this product are all on the TSCA inventory list.

### Ingredient Related Regulatory Information:

SARA Reportable Quantities	CERCLA RQ	SARA TPQ
2-Methylpropane(R600a)	NE	

## 16 OTHER INFORMATION

Revision Information  
Revision Date  
Supercedes Revision Dated  
Revised section 9.  
Revision Summary

20 SEP 2001

13-JUL-2000

Revision Number 6

### Key

NE= Not Established

NA= Not Applicable

(R) = Registered Trademark

### Miscellaneous

This MSDS applies to the following grades:

Isobutane R600a - Appliance Grade

Isobutane R600a

We believes that the information and recommendations contained herein (including dataand statements) are accurate as of the date hereof. NO WARRANTY OF FITNESS FOR ANY PARTICULAR

PURPOSE, WARRANTY OF MERCHANTABILITY, OR ANY OTHER WARRANTY, EXPRESSED OR

IMPLIED, IS MADE CONCERNING THE INFORMATION PROVIDED HEREIN. The information provided herein relates only to the specific product designated and may not be valid where such product is used in combination with any other materials or in any process. Further, since the conditions and methods of use are beyond the control of Chemicals, Chemicals expressly disclaims any and all liability as to any results obtained or arising from any use of the product or reliance on such information.